

General information

Available protocols
for communication

- GSM

Particulate matter concentration measurement

	Range	Resolution
PM1.0	0 – 500 µg/m³	± 1 µg/m³
PM2.5	0 – 1000 µg/m³	± 1 µg/m³
PM10	0 – 1000 µg/m³	± 1 µg/m³

Measurements interval

- Airly PM Sensor: 5 min
- Airly PM+GAS Sensor: 5 min

Power supply

- Powered by: 5V@2A from external USB Power supply: (230V/110V)
- Power supply cable length: 2.9 m
- Solar power supply: available
- Average power consumption: 1.2 W
- Max. power consumption: 2 W
- Energy consumption (per 24h): 0.03 kWh
- Energy consumption (per year): 10.5 kWh

Data accessibility

- Airly website map.airly.org
- Airly Mobile app iOS, Android and Huawei
- Widget
- Airly API
- Airly Data Platform (ADP)

Installation requirements

- GSM range: min -90 dBm
- Access to power: The sensor must be permanently connected and powered if you can't meet this recommendations for your destination, consider using the sensor with the power system solar energy.
- Height: 1.5 – 8 m above the ground



Airly sp. z o.o.
ul. Mogilska 43
31-545 Kraków
Poland

contact@airly.org
map.airly.org
airly.org

Technical specification



Airly PM Sensor

Airly PM+GAS Sensor

Constant working conditions				
Temperature	-40°C – +80°C		-40°C – +80°C	
Humidity	0 – 100%		0 – 100%	
Pressure	700 – 1 200 hPa		700 – 1 200 hPa	
Measurements				
	PM1, PM2.5, PM10, temperature (°C), pressure (hPa), humidity (%)		PM1, PM2.5, PM10, temperature (°C), pressure (hPa), humidity (%)	
			types: NO ₂ +O ₃ , SO ₂ +CO, NO ₂ +NO	
	Range	Resolution	Range	Resolution
Temperature	-40°C – +80°C	± 0,1°C	-40°C – +80°C	± 0,1°C
Pressure	700 – 1 200 hPa	± 1 Pa	700 – 1 200 hPa	± 1 Pa
Humidity	0 – 100%	± 1%	0 – 100%	± 1%
Measurement frequency				
Sampling Interval	1-2 sec		1-2 sec	
Averaging Interval	5 min		5 min	
Sending interval	5 min		15 min (3 samples with a 5-minute average)	
Both sensors (in Low Power mode)	Sampling Interval 1-2 sec every 4 min	sending interval 20 min	Sleep time 16 min	
Gas concentration measurement			Range	Resolution
NO			0 – 5 000 ppb	± 1 ppb
NO ₂			0 – 5 000 ppb	± 1 ppb
O ₃			0 – 5 000 ppb	± 1 ppb
SO ₂			0 – 5 000 ppb	± 1 ppb
CO			0 – 20 000 ppb	± 1 ppb
Enclosure parameters and weight				
Case material	Stainless steel		Stainless steel	
Dimensions	74 x 77* x 83,5 mm		74 x 112* x 83,5 mm	
Device weight	440g		490g	

